

NAVIGATOR

FOR PERFECTIONISTS, BY PERFECTIONISTS.

The Navigator®'s integrated collection system picks up clippings, lengthens emptying intervals and leaves premier properties looking their best. We take pride in the fact that anything bearing the Exmark® name is an exceptional piece of equipment. You can feel confident knowing that it's the brand landscape pros choose 2 to 1 over any other. Visit exmark.com

DECK

STYLE — Full-floating, center-discharge standard with two-sided trimming.

WIDTHS AVAILABLE

42" or 48" 7-gauge sides joined by a continuous bead weld to a 10-gauge top, 3/16" wear guard is welded to the entire base of the deck, 7-gauge deck spindle supports, 0.25"-thick strap steel deck supports.

CUTTING HEIGHTS

1.0" (2.5 cm) to 4.0" (10.2 cm) in 0.25" (0.64 cm) increments.

BLADE

0.164"-thick blades with 3 1/2" air foil.

BLADE DRIVE

1" Austempered spindle shaft with shear-pin protection at the blades.

BLADE-TIP SPEED

Approximately 18,500 fpm.

TRACTOR FRAME

Channeled and fully welded 1.5" x 1.5" x 0.187" wall tubing with a ground clearance of 4.0," strategically located, continuous force counterweight springs.

STEERING & MOTION CONTROL

"FeatherTouch" hand-control drive levers, low-force constant speed lever.

FRONT CASTER TIRES

8 x 3.0-4 semi-pneumatic.

REAR CASTER TIRES

13 x 8.0-6 semi-pneumatic.

DRIVE TIRES

18 x 10.5-10 Multi-Trac® C/S.

TURNING RADIUS

True zero-turn.

PARKING BRAKE

Wet disc, internal in wheel motor.

SEAT

High-back, "EVC" (Elastomeric Vibration Control) seat, which has no springs to break.

ENGINES AVAILABLE

20 or 27 hp Kohler® Command™ SP, governed to 3,600 rpm.

ENGINE HOURMETER

Standard.

DRIVE SYSTEM

Dual Hydro-Gear 12 cc variable displacement pumps power Hydro-Gear Planetary Reduction motors.

SPEED

Infinitely variable speed selection from 0–7.0 mph (11.3 kmph) forward, 0–5.5 mph (8.9 kmph) reverse.

PTO ENGAGEMENT

Clutching belt with 6" brake band.

FUEL CAPACITY

7.5-gallon (28.4-L), pivoting tank for easier engine service.

HYDRO FLUID

Exmark Premium Hydro Oil.

GROUND CLEARANCE

4" from base of tractor frame.

GEARBOX DESIGN

Heavy-duty cast iron. Three independently sealed high-capacity gearboxes with spiral bevel-cut gears for quiet operation.

BLOWER

5.0" x 11" x 1/4" housing with reinforced high-wear areas and a three-blade abrasion-resistant impeller.



MOWS UP TO **3.4**
ACRES PER HOUR

GROUND SPEEDS UP
TO **7.0 MPH**

NAVIGATOR

MODEL	ENGINE	CUTTING WIDTH
NAV20KC	20 hp Kohler Command	
NAV27KC	27 hp Kohler Command	
CD42CD		42" (107 cm)
CD48CD		48" (122 cm)

BEST-SELLING BRAND OF MOWING EQUIPMENT FOR THE LANDSCAPE PROFESSIONAL.

EXMARK MANUFACTURING COMPANY INC. • 2101 Ashland Avenue • P.O. Box 808 • Beatrice, NE 68310-0808 Call 402.223.6300 • Fax 402.223.6384
Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Navigator® are registered trademarks of Exmark Mfg. Co., Inc. ©2010 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2010.

exmark
exmark.com